



MAQUINARIA AGRÍCOLA SEGUÉS S.L.

Avda. Santuari s/n  
25215 SANT RAMON  
(Lleida)  
Tel.: +34 973 52 43 36  
Fax: +34 973 52 43 81

[www.seguessl.com](http://www.seguessl.com)  
[segues@seguessl.com](mailto:segues@seguessl.com)  
[recanvis@seguessl.com](mailto:recanvis@seguessl.com)  
[export@seguessl.com](mailto:export@seguessl.com)  
[administracio@seguessl.com](mailto:administracio@seguessl.com)



# RA-TM

GREAT VOLUME, TWIN SPINNER  
AND PULL TYPE FERTILIZER  
SPREADERS



[www.seguessl.com](http://www.seguessl.com)

[www.seguessl.com](http://www.seguessl.com)

## Twin disc, pull type and with conveyor belt Fertilizer Spreaders RA-TM 10, 15 i 20 SPREADERS



### SEGUÉS, performing the fertilization since 70's

"The RA-TM fertilizer spreaders series offer the high precision that defined Segué's since the first spreader, put together with new improving systems, high capacity hoppers and also the biggest in the market, and electronic distribution systems to reach a perfect VRA."

#### RA-TM Fertilizer spreaders strong points:

- Hydraulically driven Spinners
- RA-TM10 fitted with mechanical VRA system
- RA-TM15 & 20 fitted with electronic VRA system
- Very width conveyor belt to avoid the vault effect in the product
- Great diameter spinners capable to spread from mineral to powdered organicals
- Traction tyres for a lower soil compactation and better pull.
- In RA-TM15 & 20, tandem with one fixed and one self steering axle.
- Front window to view inside the hopper
- Sprung drawbar for a better pull
- Hopper acces stairs.

#### STANDARD EQUIPMENT



Sprung Draw Bar



Inside hopper viewing window



spinners hydraulically driven



Tandem and self-steering axle in RA-TM15 & 20



Hydraulic brake and mechanical parking brake



Mechanical VRA system in RA-TM10



Mechanical jack in RA-TM10 & 15 and hydraulic jack in RA-TM20



Electronic VRA system in RA-TM 15 & 20

#### TECHNICAL FEATURES

Model	Tare	Hopper	Width	Height	Length	Tyres
RA-TM 10	3.280 kg	8.500 l	2.420 mm	2.540 mm	5.780 mm	520/70R34
RA-TM 15	5.420 kg	12.750 l	2.500 mm	2.830 mm	7.492 mm	18.4/15-30
RA-TM 20	6.640 KG	17.000 L	2.804 mm	3.000 mm	8.530 mm	520/70R34

#### AVAILABLE NON-STANDARD OPTIONS FOR RA-TM SPREADERS

- + "INTELLIGENT" electronic VRA system
- + ISOBUS electronic control system
- + Hydraulic cover RA-TM15 and sliding RA-TM20
- + Spinner selector
- + Inside hopper auger for compost fertilizers
- + Distribution system for mineral fertilizer
- + Top screen made of galvanized steel
- + Working width adjusting system